How to apply **Vinyl lettering**





See our How 2 Reading Hour Vinyl application video at http://goo.gl/3qZag

Application requirements:

- Masking tape
- Anything with a flat, straight edge e.g. ruler, credit card, spatula
- Measuring tape or ruler

Lettering sheets consist of three layers:

- Top Layer Transfer paper through which you can see the letters
- Middle layer The letters
- Bottom layer -Backing paper

Application steps:

- Clean surface and ensure it is dry before commencing application.
- Place your lettering sheet in your desired location.
- **3** Use small pieces of masking tape to hold it in place.
- Ensure that the letters are straight by measuring to the letters (not the edge of the sheet) from the floor, ceiling or a known straight edge. Adjust the sheet and masking tape pieces as needed.
- Once letters are straight, place a long piece of masking tape along the entire top edge of your lettering sheet.
- Flip up the lettering and peel off the backing paper, be careful that all the lettering remains attached to the transfer paper. The masking tape is now working as a hinge.

- Slowly lower the lettering sheet and gently rub over the lettering sheet (with straight edge implement) to adhere to the chosen surface. Work from the top centre down and out, making sure to force the bubbles out as you go.
- Firmly rub over the lettering (with straight edge implement) to securely adhere to the chosen surface. Work from the top centre down and out
- **9** Leave for an hour to adhere to the surface.
- Carefully peel off the transfer paper to reveal your letters. If you notice any letters are pulling up with the transfer paper, re-rub onto the surface.

For large lettering:

For large single horizontal words:

After completing step 5 of the application instructions, cut between every 2 to 3 letters from the bottom of the sheet up to the masking tape holding the sheet in place at the top. This will leave you with smaller sections to apply making it easier to complete installation.

For large multiple words:

Prior to beginning the application, cut the sign into manageable sized pieces, preferably keeping words and if possible lines in one piece. Now begin the application following the step by step instructions. If the lines are still too long to handle follow the first suggestion as well.

For application to windows:

Prepare a small spray bottle with a solution of warm water with a couple of drops of dishwashing liquid. After completing step 6 in the application instructions, spray a mist of the solution on to the window surface where you will be applying the lettering. The solution makes it easier to remove bubbles. Continue on with step 7 as per the instruction.

Please note: small bubbles will settle over a period of 1-2 weeks. Large bubbles can be pierced with a pin and the air can be worked out of the hole